

ELECTRONICS FOR SPORT

FOS-26 (Art.300-26)

Outdoor Scoreboard for Football/Soccer.

Functions displayed:

Game time: [00:00 - 99:59], digits 45cm high. Team scores: [0-9], digit 45cm high. Time of day: displayed when the control console is turned off or disconnected.

Technical characteristics:

Dimensions and weight: 166,5x118x15cm, 46kg.

For outdoor use. Resistant to bad weather. Works in temperatures of -20°C to +50°C.

• Distance and readability angle: 200m, 130 degrees.

 Good visibility even in direct sunlight. Each 45cm digit is composed of 264 SMD LEDs with 1cd of brightness each and an average life of 100,000 hours. The brightness of the scoreboard can be adjusted for dimming during evening hours via the command Item codes and prices (not including VAT) console (see ACCESSORIES).

 No front protection cover required. Complies with DIN 18032-3 and UNI 9554:1989 standards on "resistance to damage from balls." You save on the cost of a protective cover, visibility is completely preserved, and access to the scoreboard is easy. YouTube video

 Resistant to acts of vandalism. The front panel cannot be broken or damaged by rocks or moderate-sized objects thrown at it.

 Game timer. Using the Control Console (see ACCESSORIES) you can choose different operation modes depending on the sport selected: game and interval time, count back or forward, display last Clock. The time of day is automatically displayed when the

console is turned off or disconnected. The clock's internal battery has a life of 20 years!

The horn can be sounded manually or automatically when the time expires, producing a strong acoustic signal (120dB at 1m) with adjustable duration and intensity.

• Shipping is cheap and fast. The scoreboard is especially designed to be taken apart into smaller modules that are easy to assemble. This allows it to be shipped via all major couriers at a low cost and with faster delivery times to all countries

 Technical instructions in 5 languages: English, French, Spanish, German, Italian.

 Robust container made from powder-coated aluminum. Front panel made from polycarbonate.

 Supplied with serial cable to connect to the Control console, 50m long or chose from different lengths when ordering. Alternatively, a Radio Receiver is available (art.302-02) that allows you to save on the cable costs installation (see ACCESSORIES).

Conformal Coating (anti-moisture) of the electronic boards.

Guarantee: 2 years (info).

• Power supply: 100-240Vac, 50-60Hz, 170VA. Select the type of plug for the power supply cord when ordering.

ACCESSORIES (not included):

Scoreboard Control Console: Art.308-01 Console-700

User-friendly multisport touchscreen console for FC, FS, FW, TM, FOS series electronic scoreboards. Wireless or wired communication. 14-hour average life internal battery.

• Radio Receiver for FOS scoreboards (art.302-02). It is intended to be mounted above the scoreboard and receives the data transmitted by the control console, when equipped with a radio transmitter, which helps to avoid cable costs. Reliable wireless communication: by 2.4GHz FHSS (Frequency Hopping Spread Spectrum) radio transmission to avoid interferences. The use of a wireless system reduces costs by eliminating the need of a cable connection between console and scoreboards. Radio range up to 300m without obstacles. >> FOS2 Radio Receiver installation manual

FAVERO ELECTRONICS Srl - Italy - www.favero.com - tel +39 0422 874140 - Email : favero@favero.com - 29/04/2024



Art.300-26 FOS-26 Outdoor scoreboard Size: 166,5X118X15cm. - Weight: 46kg.



Art.308-01 EUR 720.00 Console-700, multisport console with 7 touchscreen display Size: 24.5x17x8.5cm. - Weight: 1.35kg.



Art.308-10 EUR 66.00 Case-700, carrying case for Console-700 2014-05-22 Size: 40x30x13.5cm. - Weight: 1.53kg.



Art.302-02 EUR 263.00 FOS2 Radio receiver for FOS-series scoreboards Size: 16x12x8cm. - Weight: 1kg.