

bePRO S (Art.771-10)

Bicycle power meter with a single power sensor.

Integrated in only one pedal, bePRO S measures the force applied on the left pedal and provides an estimation of the total power exerted by both legs. Cyclists who wish to have top power measuring can **buy the right pedal separately at a later time.**

bePRO S has an **internal integrated cadence sensor.**

Overview:

• Light

The use of high tech content and cutting-edge materials, the weight of the bePRO S sensor is only **16 g**, makes the powemeter extremely light, total weight of each pedal is only **156 g**.

• Rechargeable

Your power meter is always ready for use. Its rechargeable lithium-ion batteries have a **30-hour life**, regardless of whether you are racing or training.

• Reliable

Reliable even in **extreme conditions** as proved by the rigorous quality tests successfully passed by bePRO S: impact, drop, wear, water, temperature and humidity tests.

• Compatible

Thanks to the **ANT+** technology, bePRO S is compatible with the best cycling computers available on the market. The power meter software ensures reliable data transmission from the power meter to any commercially available device.

• Easy to install

You can install your bePRO S on your bicycle **by yourself in just a few minutes**, without the assistance of a mechanic, without needing to modify the transmission, remove the wheels, or install external sensors.

• Accurate

Provided with an advanced compensation system, bePRO S can take accurate and reliable measures **in any environmental condition**, with a margin of error of only 2%.

Technical characteristics:

- Radio transmission protocol: ANT+, 2,4 GHz
- Sent parameters: instantaneous power (Watt), instantaneous cadence (rpm)
- Minimum - maximum power: 0 - 2000 W
- Minimum - maximum cadence: 30-180 rpm
- Power measuring accuracy: $\pm 2\%$
- Cadence sensor: internal integrated
- Internal battery: 30-hour life rechargeable lithium battery
- Weight of the pedal with sensor: 156 g
- Sensor weight: 16 g
- Pedal weight: 140 g
- Pedal bolt material: Cr-Mo steel
- M16 nut material: AISI 316L steel
- Pedal body material: NEP injection molded
- Threading: 9/16"-20 tpi
- Bearings: n.3 sealed cartridge bearings
- Minimum - maximum operating temperature: -10 / 60 °C
- Water resistance: IPX7
- Pedal maximum charge: 120 kg
- Battery charger: inlet 100-240 V, 50/60 Hz, 85 mA - outlets 2xUSB 5V 1,0A
- Battery charger plugs adaptor: EU, US, UK, AU (IEC Types C, A, G, I)
- Certifications: CE, RoHS, ANT+ PWR
- Reference standards: EN14038, EN60950
- Compatible cleats: Look Keo
- Guarantee: 2 years

Package content:

- Left pedal with power sensor
- Right pedal with power sensor
- Look Keo (6°) compatible cleats
- Battery charger supplied with two 2 meter-long cables
- Set 2 bePRO alignment labels
- Set installation tools



Item codes and prices (not including VAT)



Art.771-10

...bePRO S

This model is out of stock and it is NO MORE PRODUCED.

Weight: 0.285kg.

- User manual
- Package size and weight: 405x100x105mm 1.7 kg

Optional accessories (not included):

- Crowfoot adapter for torque wrench 3/8" (art.771-82)
- Right side pedal with powermeter as upgrade from bePRO S to bePRO (art.771-55)

Quick links:

- [User manual](#)
- Configuration software
- [Spare parts](#)

For more info visit www.bepro-favero.com.

ATTENTION:

Buying on this website is reserved solely for Resellers.
If you are not a Reseller, you can buy the bePRO on the
www.bepro-favero.com website
Prices shown in this site do not include VAT or export costs.

FAVERO ELECTRONICS Srl - Italy - www.favero.com - tel +39 0422 874140 - Email : favero@favero.com - 08/05/2024