

CT42w, CT62w

Prepaid card Timers for 4-6 showers. Version with RFID contactless reader.

Uses OLED graphic display.

art.187-42 **CT42w** - for 4 showers ([foto](#))

art.187-62 **CT62w** - for 6 showers ([foto](#))

- **Place the prepaid cards, wristbands or key rings on the RFID reader to activate the solenoid valves.**
- Includes a 12Vdc output for **direct activation of a solenoid valves**, which must be purchased separately (art. 199-20).
- The **CT** includes a separate **relay unit**. In this way the **CT** can be placed in a convenient location for service customers. The **relay unit** can be positioned so as to reduce the length of electrical cables to the showers.
- It is possible to **delay the start of service**, in order to save water prior to using the service.
- **Accumulation of time** feature possible. If enabled, the service time available can be increased (max. 48 hours) by placing the TAG/transponders more than once. If feature is disabled, no increase of available time can be effectuated and no credit adjustment in the RFID TAGs will occur.
- A **light display** (OLED) helps to illuminate the cost of the service when in use, the remaining time, and facilitates configuration.
- **Multilingual:** There are 5 languages to choose from (English, French, Spanish, German), facilitating easier comprehension of product instructions and use.
- **Start/Pause buttons** can be connected externally, enabling the customer to activate or stop the supply of water and regulate the pauses for lathering. The maximum time for a pause can be adjusted.
- The function "**end of water notice**" (automatic pause) causes a brief interruption of water to occur. This is useful for warning the customer of the remaining time available and for allowing sufficient time to finish bathing.
- **The counting time is memorized** in case power supply is interrupted and will automatically resume when power is restored. This prevents the time from being reset when brief interruptions occur and from any ensuing complaints.
- The function "**end of service notice**" utilizes a special output to warn customers of the end of service without interrupting the service. In this mode every **CT** service occupies 2 outputs (relay), reducing the number of available services by half.
- The **RFID reader** allows for payment of services through the decrement of costs, and displays any remaining credit in the TAG/transponder. The code set by the administrator ensures that the payment system is safe. All TAG/transponders use RFID contactless technology without magnetic strips.
- The system requires a dedicated programmer (**Art. 193-01 CARDWRITER-01**) to load and zero the amount of the TAG/transponders. The totalizers allow for the verification of the amounts allocated.
- **Stainless steel container**, with high resistant coating for outdoors. International protection rating IP30. As an option (see OPTIONS), the **CT** can be furnished with protection from rain and water (international protection rating IP34).
- The device does not fulfill the Italian obligation of electronic recording and data transmission (Art. 2, comma 2, D.Lgs. Italiano 127/2015).
- **Size and weight of CT:** height 26 cm, width 22.5 cm, depth 14 cm, 5.2 kg. The **small dimensions** of the article reduce bulkiness and make it more aesthetically pleasing.
- **Size and weight of relay unit:** height 30 cm, width 23.5 cm, depth 12.5 cm, weight 1.9 kg.
- **Power supply CT:** 100-240V, 0.35A, 50-60 Hz. As an option, the 12Vdc version with power supply is also available (see OPTIONS).
- **Power supply relay unit:** 100-240V, 2.5A, 50-60 Hz.
- **Warranty:** 2 years ([info](#)).

OPTIONS (can be selected after adding article to basket)

- **Protection from rain and splashing water.** ([photo](#)) International protection rating IP34. This article is useful for uncovered outdoor installations or those situated where splashing water can reach them. Protection includes:
 1. Water resistant lock.
 2. Washers for door mechanism.
- **Power supply 12Vdc.** Power supply device 12Vcc is useful when the CT is installed in places where it is obligatory to use a safety extra-low voltage (SELV). It comes furnished with its own power



Item codes and prices (not including VAT)



Art.187-42
...CT42w Timer 4 showers with RFID Prepaid Card Acceptor
Size: H26x22,5x14cm. - Weight: 4.7kg.



Art.187-62
...CT62w Timer 6 showers with RFID Prepaid Card Acceptor
Size: H26x22,5x14cm. - Weight: 4.8kg.



Art.199-20 **EUR 65.00**
Solenoid valve, 12Vdc 8W max, G1/2 Female-Female, ISO-228
Size: 6x4xH10cm. - Weight: 0,50kg.



Art.199-27 **EUR 12.00**
Water Y-Strainer, size 1/2, female-female, ISO-228
Size: 6x3x5cm. - Weight: 0,15kg.



Art.199-45 **EUR 44.00**
START/STOP push-button IP65, protected against splashing water
Size: 8.5x8.9x5.8cm. - Weight: 0.21kg.



Art.199-50 **EUR 1.10**
RFID Prepaid Card
Weight: 0,005kg.

supply with a 12Vdc output and a 100-240V input, and should be installed in a place where the use of such voltage is permitted.

Articles needed for completion of a shower system

• **Solenoid valve 12Vdc 8Watt max.**

It should be inserted in the tubing or the shower spout so as to control the opening of water. Since the timer provides a 12Vdc output voltage for controlling the solenoid valve, it is therefore not necessary to purchase a power supply device for this valve. Use a common solenoid valve with 12Vdc solenoid (in direct current) and maximum absorption of 8 Watts.

If you are not in possession of such a solenoid valve, the following article can be purchased:

Art.199-20 Solenoid valve 12Vdc 8W max, G1/2" Female-Female, ISO-228.

• **Water Strainer (optional)**

Permits the filtering of impurities and particles present in the water. Its installation is advised for increasing the duration of the solenoid valve,

Art.199-27 Water Y-Strainer, size 1/2", female-female, ISO-228.



Art.199-52 **EUR 448.00**
RFID Prepaid Card - 500 pieces package
Weight: 2,700kg.



Art.199-55 **EUR 2.70**
RFID Key ring
Weight: 0,005kg.



Art.199-62 **EUR 6.00**
RFID silicone Wristband, diam.65 mm
Weight: 0,015kg.



Art.199-64 **EUR 6.00**
RFID silicone Wristband, diam.74mm
Weight: 0,017kg.



Art.193-01
CARDWRITER-01 - RFID Programmer
Size: 13,2x8,9x15,7cm. - Weight: 1,04kg.