

ELECTRONICS FOR SPORT

CT41w, CT61w

Coin, token and prepaid card operated Acceptors/Timers for 4-6-8 showers. Version with electronic coin acceptor and RFID prepaid card contactless readers.

Uses OLED graphic display.

art.187-41 CT41w - for 4 showers (photo) art.187-61 CT61w - for 6 showers (photo)

- Introduce coins or tokens, or place prepaid cards, wristbands or key rings on the RFID reader to activate the solenoid valves.
- Includes a 12Vdc output for direct activation of a solenoid valves, which must be purchased separately (art. 199-20).
- The CT includes a separate relay unit. In this way the CT can be placed in a convenient location for service customers. The relay unit can be positioned so as to reduce the length of electrical cables to the showers.
- The time of service (closing of the relay) can be easily adjusted Item codes and prices (not including VAT) from 1 second to 24 hours.
- Accumulation of time feature possible. If enabled, the service time available can be increased (max. 48 hours) by inserting coins or tokens, or by placing the TAGs/transponders more than once. If feature is disabled, no increase of available time can be effectuated: coins or tokens will be returned from the Coin Acceptor and no credit adjustment in the RFID TAGs will occur.
- It is possible to delay the start of service, in order to save water prior to using the service.
- A **light display** (OLED) helps to illuminate the cost of the service when in use, the remaining time, and facilitates configuration.
- Multilingual: There are 5 languages to choose from (English, French, Spanish, German), facilitating easier comprehension of product instructions and use.
- Start/Pause buttons can be connected externally, enabling the customer to activate or stop the supply of water and regulate the pauses for lathering. The maximum time for a pause can be adjusted.
- The funtion "end of water notice" (automatic pause) causes a brief interruption of water to occur. This is useful for warning the customer of the remaining time available and for allowing sufficient time to finish bathing.
- The counting time is memorized in case power supply is interrupted and will automatically resume when power is restored. This prevents the time from being reset when brief interruptions occur and from any ensuing complaints.
- Coins inserted when the CT is not in service will be rejected and returned, thereby preventing disputes from customers.
- The CT uses an electronic comparable coin Acceptor which is easily programmable to accept any type of coin or token. Simply place a sample coin or token in the appropriate slot of the Acceptor and the coin/token will serve as a reference for all other coins/tokens inserted. It is easy then to change the type of coin that the CT will accept. As an option (see OPTIONS) the **CT** can also come with an electronic multi-coin Acceptor, useful for accepting various types of coins at the same time. For more information see OPTIONS.
- The function "end of service notice" utilizes a special output to warn customers of the end of service without interrupting the service. In this mode every CT service occupies 2 outputs (relay), reducing the number of available services by half.
- The RFID reader allows for payment of services through the decrement of costs, and displays any remaining credit in the TAG/transponder. The code set by the administrator ensures that the payment system is safe. All TAG/transponders use RFID contactless technology without magnetic strips.
- The system requires a dedicated programmer (Art. 193-01 CARDWRITER-01) to load and zero the amount of the TAG/transponders. The totalizers allow for the verification of the amounts allocated.
- Stainless steel container, with high resistant coating for outdoors. International protection rating IP30. As an option (see OPTIONS), the CT can be furnished with protection from rain and water (international protection rating IP34).
- Large coin drawer that can hold circa 400-500 coins/tokens.
- The device does not fulfill the Italian obligation of electronic recording and data transmission (Art. 2, comma 2, D.Lgs. Italiano
- Size and weight of CT: height 26 cm, width 22.5 cm, length 14 cm, weight 5.2 kg. The **small dimensions** of the article reduce bulkiness and make it more aesthetically pleasing.
- Size and weight of relay unit: height 30 cm, width 23.5 cm, depth 12.5 cm, weight 1.9 kg.







Art.187-41

CT41w Timer 4 showers with Coin and **RFID Prepaid Card Acceptor** Size: H26x22,5x14cm. - Weight: 5.2kg.



Art.187-61

CT61w Timer 6 showers with Coin and **RFID Prepaid Card Acceptor** Size: H26x22,5x14cm. - Weight: 5.3kg.



Art.R200-2 EUR 0.70

TOKEN monometallic Size: diam. 26.6mm, spess. 2mm -- cm. -Weight: 0.0085kg.



Art.199-20 EUR 65.00

Solenoid valve, 12Vdc 8W max, G1/2 Female-Female, ISO-228 Size: 6x4xH10cm. - Weight: 0,50kg.



Art.199-27 EUR 12.00

Water Y-Strainer, size 1/2, female-female, ISO-228

Size: 6x3x5cm. - Weight: 0,15kg.



Art.199-30 EUR 42.00

Cover for Coin Acceptor

Size: H13.2x6.8x2.4cm. - Weight: 0,16kg.

- **Power supply CT**: 100-240V, 0.35A, 50-60 Hz. As an option, the 12Vdc version with power supply is also available (see OPTIONS).
- Power supply relay unit: 100-240V, 2.5A, 50-60 Hz.
- Warranty: 2 years (info).

OPTIONS (can be selected after adding article to basket)

- **Protection from rain and splashing water.** (photo) International protection rating IP34. This article is useful for uncovered outdoor installations or those situated where splashing water can reach them. Protection includes:
- 1. Sturdy cover for coin acceptor (photo), as art.199-30.
- 2. Water resistant lock.
- 3. Washers for door mechanism.
- Power supply 12Vdc. Power supply device 12Vcc is useful when the CT is installed in places where it is obligatory to use a safety extra-low voltage (SELV). It comes furnished with its own power supply with a 12Vdc output and a 100-240V input, and should be installed in a place where the use of such voltage is permitted.
- Electronic multi-coin Acceptor.(photo) Useful for allowing the CT to accept up to 6 different types of coins. The operator can programme the coins by inserting each type of coin repeatedly. The programmed time on the CT relates to the coin of least value; the other 5 coins must have a multiple value of this. It is also possible to allow the Acceptor to accept two different coins (or one coin and one token) of the same value.

Articles needed for completion of a shower system

Solenoid valve 12Vdc 8Watt max.

It should be inserted in the tubing or the shower spout so as to control the opening of water. Since the timer provides a 12Vdc output voltage for controlling the solenoid valve, it is therefore not necessary to purchase a power supply device for this valve. Use a common solenoid valve with 12Vdc solenoid (in direct current) and maximum absorption of 8 Watts.

If you are not in possession of such a solenoid valve, the following article can be purchased:

Art.199-20 Solenoid valve 12Vdc 8W max, G1/2" Female-Female, ISO-228.

Water Strainer (optional)

Permits the filtering of impurities and particles present in the water. Its installation is advised for increasing the duration of the solenoid valve.

Art. 199-27 Water Y-Strainer, size 1/2", female-female, ISO-228.

Optional articles (not included)

Art.199-30 Cover for Coin Acceptor (photo1, photo2). Sturdy steel protection case with powder coating and cataphoresis painting, and with transparent polycarbonate window. The cover is used for protecting the coin acceptor from splashing water or sand at seaside locations.

Very easy fastening, via 2 screws only, on all CT models.



Art.199-45 EUR 44.00 START/STOP push-button IP65, protected against splashing water Size: 8.5x8.9x5.8cm. - Weight: 0.21kg.



Art.199-50 EUR 1.10 **RFID Prepaid Card** Weight: 0,005kg.



Art.199-52 EUR 448.00 **RFID Prepaid Card - 500 pieces package** Weight: 2,700kg.



Art.199-55 EUR 2.70 **RFID Key ring** Weight: 0,005kg.



Art.199-62 EUR 6.00 **RFID silicone Wristband, diam.65 mm** Weight: 0,015kg.



Art.199-64 EUR 6.00 **RFID silicone Wristband, diam.74mm** Weight: 0,017kg.



Art.193-01 EUR 330.00 CARDWRITER-01 - RFID Programmer Size: 13,2x8,9x15,7cm. - Weight: 1,04kg.

FAVERO ELECTRONICS Srl - Italy - www.favero.com - tel +39 0422 874140 - Email : favero@favero.com - 11/05/2025